



## INDUSTRIAL VACUUM CLEANER SYSTEM

# NEW

# GS 3/78 OPT CYC

Equipped with 3 high airflow motors, this model is designed for vacuuming large amounts of dusts and debris and guaranteeing constant suction performances. The integrated cyclonic system, with H14 Hepa cartridge filter and M class pre-filter bag, ensures a high filtration efficiency avoiding clogging problems while vacuuming. The lightweight stainless steel tank with detachable 78 liters recovery tank and the sturdy trolley with large braking wheels guarantee a high maneuverability during cleaning operations.

### EXCLUSIVE FEATURES

- ▶ MODERN INDUSTRIAL DESIGN
- ▶ STRONG AND LIGHTWEIGHT TROLLEY WITH TOP MANUVRABILITY ON ANY TYPE OF FLOOR
- ▶ BIG RUBBER WHEELS WITH BREAKES
- ▶ TILTING TANK DETACHABLE, EASY TO EMPTY
- ▶ 3 HIGH AIRFLOW MOTORS WITH BEST PERFORMANCES
- ▶ HEPA H14 CARTRIDGES AND CLASS M BAG
- ▶ CYCLONIC SYSTEM WITH 95% EFFICIENCY
- ▶ CONDUCTIVE INLET TO GROUND STATIC ELECTRICITY



### MOST FREQUENTLY USE

GRANULAR SOLIDS: 100%



SAND MATERIAL: 90%



BULKY MATERIALS: 80%



GENERIC DIRTY: 75%



FINE DUST: 50%



COMBUSTIBLE DUST: 0%



MIXTURES WITH WATER: 0%



OIL NOT FLAMMABLE: 0%



### SPECS



CYCLONE SYSTEM



TIPPING TANK



HEPA H14 CARTRIDGE



MICROFIBRE BAG



DETACHABLE TANK SYSTEM



LARGE REAR WHEELS WITH TYRES FOR WORKING ON UNEVEN SURFACES

TECHNICAL DATA

|                      |                    |                 |       |
|----------------------|--------------------|-----------------|-------|
| d                    |                    | GS 3/78 OPT CYC |       |
| PERFORMANCE          |                    | A               | 1 6 6 |
| Usage                |                    | Dry             |       |
| Motor                |                    | 3               |       |
| Type of motor        |                    | Single stage    |       |
| Nominal Power        | W                  | 3400            |       |
| Voltage / Frequency  | V / Hz             | 220-240 / 50-60 |       |
| Waterlift            | mmH <sub>2</sub> O | 2230            |       |
| Airflow              | m³/h               | 765             |       |
| Tank Gross Capacity  | l                  | 78              |       |
| Tank material        |                    | Stainless Steel |       |
| Cable length         | m                  | 8               |       |
| Filtering surface    | cm²                | 2200            |       |
| Sound Pressure Level | dB(A)              | 76              |       |
| Øeter of inlet       | mm                 | 50              |       |
| Weight               | kg                 | 80              |       |
| Dimensions           | mm                 | 600x620x1335    |       |

## OPTIONAL ACCESSORIES KIT

### COMPLETE MULTIPURPOSE PREMIUM TOOL KIT 3 M Ø38 MM COMPOSED OF:

CONDUCTIVE PU FLEXIBLE  
HOSE 3 m Ø38 mm



PLASTIC TUBE 50 cm  
(MACHINE COMES WITH  
2 PCS)



DOUBLE STEEL WAND  
Ø38 mm



FLAT LANCE Ø38 mm



ROUND BRUSH  
Ø38 mm



BRUSH Ø38 mm WITH  
INTERCHANGEABLE  
SLIDES



### COMPLETE MULTIPURPOSE PREMIUM TOOL KIT 4 M Ø50 MM COMPOSED OF:

CONDUCTIVE PU FLEXIBLE  
HOSE 4 m Ø50 mm



COMPLETE ALUMINIUM  
DOUBLE WAND Ø50 mm



RUBBER FLAT LANCE  
Ø50 mm



BRISTLE BRUSH Ø50 mm



SQUEEGEE X2 PCS



### COMPLETE STATIC DISSIPATIVE TOOL KIT 5 M Ø50 MM COMPOSED OF:

CONDUCTIVE FLEXIBLE  
HOSE 5 m Ø50 mm



COMPLETE ALUMINIUM  
DOUBLE WAND Ø50 mm



RUBBER FLAT LANCE  
Ø50 mm



BRISTLE BRUSH Ø50 mm



### CONDUCTIVE KIT 2 OPERATORS Ø38/60 MM COMPOSED OF:



### COMPLETE STATIC DISSIPATIVE TOOL KIT 4,5 M Ø38 MM COMPOSED OF:

CONDUCTIVE FLEXIBLE  
HOSE Ø38-60 WITH  
CUFFS 4,5 m



DOUBLE STEEL WAND  
Ø38 mm



BRISTLE BRUSH Ø38 mm



CHROMED FLAT LANCE  
Ø38 mm

